

DESCRIPTION

The DA-250DH is a 2-Channel Digital Power Amplifier designed for 100 V line high-impedance distribution and features lightweight, compact, high power output, and high efficiency. It delivers 250 W × 2 channels (40 Ω output) using a switching power supply. Each channel is equipped with an independent power section. It can be electrically isolated from the high-impedance speaker system by attaching the MT-251H Output Transformer (optional). It can be mounted in an EIA Standard equipment rack (1 unit size).

SPECIFICATIONS

*0 dB = 0.775 V

Power Source	220 - 240 V AC, 50/60 Hz
Amplification System	Class D
Power Consumption	120 W (based on EN standards) 580 W (rated output 100 V line, 40 Ω × 2)
Input	2 circuits, +4 dB* (1.23 V) (input level control in maximum position), 10 kΩ, electronically-balanced, removable terminal block (3 pins), XLR-3-31 type connector CH 1 mode ON/OFF switch (ON: PARALLEL, OFF: STEREO)
Rated Output	2 channels: 250 W × 2 (100V line, 40 Ω) M4 screw terminal, distance between barriers: 8.8 mm (0.35")
Frequency Response	50 - 20,000 Hz (-3 dB, +1 dB)
Total Harmonic Distortion	0.1% (1 kHz) 0.3% (100 - 20,000 Hz)
Protection Circuit	Protection against excessive current flow due to overload, short circuit, unusual DC voltage output, temperature rise at power amp. heat sink (100°C or more (212°F)), temperature rise inside the unit (80°C or more (176°F))
S/N Ratio	100 dB (A-weighted)
Crosstalk	70 dB (A-weighted)
LED Indicator	Power (blue) × 1, Input (green) × 2, Output (yellow) × 2, Peak (red) × 2, Protect (red) × 2
Cooling	Forced air cooling
Operating Temperature	-10°C to +40°C (14°F to 104°F)
Operating Humidity	90% RH or less (no condensation)
Finish	Panel: Aluminum, black, alumite Case: Plated steel sheet
Dimensions	482 (W) × 44 (H) × 401.8 (D) mm (18.98" × 1.73" × 15.82")
Weight	5.3 kg (11.68 lb)
Accessory	Power cord (2 m (6.56 ft)) ...1, Removable terminal plug (3 pins) ...2, Tamper-proof cap ...3, Rack mounting screw (with plain washer) ...4
Option	Matching transformer: MT-251H

APPEARANCE

